urovo

DT66

EnterpriseMobile Computer

- 6.5-inch ultra-high-definition (720*1600) thin-bezel display, offers more information at one page and less scrolling.
- Supports in-display and backside NFC reading to meet diverse usage needs.
- The 5000mAh smart battery with a built-in battery management system enhancing overall battery life. With the hot swap feature, it achieves uninterrupted 24-hour operation.
- Powered by the latest Qualcomm 2.4GHz high-performance processor, it delivers exceptional processing speed, further empowering faster decoding of 1D/2D/DPM barcode.
- Wi-Fi 6E and 5G delivers the super fast and reliable wireless connections.
- Optional iToF camera for three-dimensional volume measurement of parcel.



2.4GHz Processor

Android 13 O.S.

IP68 Sealing

6.5-inch Display

5000mAh Smart Battery

Optional Accessories:



Trigger Handle



4-Slot Battery Charging Cradle



Charging Cradle

DT66 Enterprise Mobile Computer

Specifications

Processor
Octa-core 2.4 GHz

O.S.
Android 13,
upgradable to Android 17
Support GMS/AER

Memory
RAM: 4GB ROM: 64GB
RAM: 8GB ROM: 128GB (optional)
Micro-SD card, Up to 256 GB

Display
6.5 inch display,
720*1600

Touch Screen
Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers

Dimensions
175.8 mm L x 76.5 mm W x 14.5 mm D
Weight: About 283g

Scanning
Professional scan engine
Support international standard 1D/2D barcode;
Support barcode displayed on screen

Camera
Front: 5MP FF;
Rear: 13MP PDAF
Optional iToF camera

Sensors
Light + Accelerator+ Proximity + Geomagnetic + Gyro+ Pressure(optional)

Audio
Dual-Microphone with noise cancellation,
1.5W speaker for loud noise,
reciever supports echo cancellation

Battery
Capacity: 3.85V 5000mAh
Support hot swap

Buttons
PWR button
Vol +/- button
Scan button*2
Custom button

Slots
Nano- SIM x 2,
Micro-SD Slot x 1,
(Reserved support eSIM)

Communication
5G/4G/3G/2G
Bluetooth: BT5.2 + BR/EDR + BLE
Wi-Fi: Wi-Fi 6E，2.4G/5G
Support 2x2 MU-MIMO，
IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax
Roaming：802.11r
(Over the Air);OKC/;PMKID caching

Positioning
GPS
BEIDOU
GLONASS
Galileo

Protection
IP68
1.5m drop resistance

Environmental
Operating Temp.: -20 ~ +60°C
Storage Temp.: -40 ~ +70°C
Humidity: 5%RH ~ 95%RH(No condensation)
ESD: +/-15kv Air; +/-8kv contact

*This page is subject to change without prior notice

UROVO PTE. LIMITED
Website: en.urovo.com
Email: urovo@urovo.com
Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Singapore 048616

Urovo Europe
Website: europe.urovo.com
Email: sales-europe@urovo-emea.com
Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America
Website: us.urovo.com
Email: urovo@urovo.com
Address: 1990 Main Street, Suite 750, Sarasota, Florida 34236